



Voice Picking System

Canceling Noise Wired Headset

WHS2 Wired Version



PHYSICAL CHARACTERS

Weight	130g (with Over-the-head Headband) ; 125g (with Behind-the-neck Headband)
Wearing styles	Over-the-head headband ; Behind-the-neck headband
Field Replaceable Parts	Headband, Ear pad, Windsock, Headband pad, Temple pad, USB Type-C Cable
Interface	3.5mm audio jack socket, effort for a disconnection not less than 1 kg (Support 3.5mm audio interface to USB Type-C)
Cable	Replaceable and frost-resistant USB Type-C cable

SPECIFICATIONS

Model	CNH2
Minimum work temperature	-30°C
Minimum storage temperature	-30°C
Maximum work temperature	50°C
Maximum storage temperature	50°C
Protection grade	IP54
Humidity	5%-95% non-condensing
Microphone	High performance sealed canceling noise microphone, echo cancellation
Noise Reduction Rating	Approximately 10 dB ambient passive noise reduction
Microphone Sensitivity	-53dB (1kHz, 1Pa) , no more than 1m
Receive Frequency Response	300 Hz to 6 kHz
Speaker Sensitivity	89 dB SPL with 1.0Vrms @1 kHz
Drop resistance	12 drops from 2.2m at minimum and maximum operating temperatures 24 drops from 1.9m at minimum and maximum operating temperatures



Simique Corp.

www.simiquecorp.com

inquiry@simiquecorp.com