



Simique VPS Wearable Terminal WET3

ADVANTAGE CHARACTERISTIC

FEATURES AND BENEFITS

Dedicated Device for Simique Voice Applications

Optimized for the Simique wearable voice system, featuring an industrial-grade Android operating system for simple operation.

Rich Hardware Configuration for Various Simique VPS Multi-Mode Application Scenarios

Equipped with a 3.2-inch golden ratio display, an industrial-grade 2D scanning engine, and autofocus front and rear cameras, easily meeting the needs of barcode scanning and Image acquisition applications.

Intelligent Compact Design with Multiple Wearing Options for Enhanced Portability and Efficiency Extremely lightweight, weighing only 140 grams, and comes with accessories such as a neck strap, armband, and retractable belt for convenience in carrying and use. The intuitive and ergonomic design allows for hands-free and eyes-free voice applications, enhancing productivity and accuracy.









TECHNOLOGY SPECIFICATIONS

SPECIFICATIONS



WET3 SPECIFICATIONS	
Model	Simique – Wearable Terminal - WET3 (include 1 non detachable Battery)
Dimensions	117mm*58mm*15.9mm
Weight	140g(Include Battery)
CPU	Quad-core 2.0GHz high-performance processor
Operating System	Android 10.0
Memory	2G RAM + 32G ROM
Display	3.2 inches, resolution 800*480 pixels
Touch Panel	Multi-mode capacitive touch panel, support multi-touch, works with gloves and wet fingers
Camera	Rear 8-megapixel camera, front 5-megapixel camera, auto focus, 800mA flash
Scanning Engine	Supports 1D/2D barcode scanning
Keyboard	Front scan button * 1, side scan button * 2, side power button * 1, side \pm volume button * 2, application customization button (task * 1, message * 1, statistics * 1), supports virtual buttons
Battery	Powered by lithium battery 3.85V, 2000mAh, non-removable
Sensors	G-sensor/Proximity sensor/Light sensor
WLAN	Wi-Fi 802.11a/b/g/n/r/ac (2.4G+5G dual-band Wi-Fi), supports fast roaming, supports Wi-Fi 5G PA amplifier
Bluetooth	Bluetooth 5.0, supports BLE
Operating Temperature	-20°C~60°C *For safety reasons, do not charge in low temperature environment
Storage Temperature	-40°C~70°C (excluding battery)
Humidity	0 ~ 95% (no condensation)
Drop Specification	1.5m concrete floor multiple drops
Tumble Drop Specification	1000 times 0.5m drum drops
Rain & Dust Sealing	IP65


Rain & Dust Sealing IP65

±15KV (air discharge), ±8KV (contact discharge) **Electrostatic discharge**

Communication Type-C *1, supports OTG Interface

 $Simique-PowerPackBatteryWithClip,\ Simique-ArmBeltWithClip,\ Simique-BeltwithClip,\ Simique-MultipleChargerCradle,\ PowerSupply,\ Simique-BeltwithClip,\ Simiq$ Accessories

SingleChargerCradle, Simique-StretchingBuckle, Simique-HangingCradle, Simique-BTButton





WET3 Optional Accessories

OPTIONAL ACCESSORIES



01

Simique-PowerPackBatteryWithClip

Provides additional power supply and charging for the WET3



Simique-ArmBeltWithClip

Allows the WET3 to be secured on the arm or shoulder

03

Simique-BeltwithClip

Allows the WET3 to be worn at the waist



04

Simique-MultipleChargerCradle

Charges 2 WET3s/batteries, seriesconnectable, shares one adapter



05

PowerSupply

YN-65WC120500W2



06

Simique-SingleChargerCradle

The WET3 single charging, includes cable and power adapter



07

Simique-StretchingBuckle

Retractable hanging strap for main unit, ties to waist & retracts.



80

Simique-HangingCradle

Neck strap & main unit cradle for scanning on-the-go.



09

Simique-BTButton

Bluetooth ring triggers scanning, compatible for easy scanning.

